



GASKET REMOVAL TOOL

AX/VX & Custom Design

We designed and manufactured a variety of ring gasket removal and installation tooling that boasts a rugged, yet lightweight design to perform under the formidable conditions of the deep sea environment. In addition to the standard configurations, we have engineered and manufactured custom Max-8 and Max-14 gasket removal and replacement tool designs that require side entry to the wellhead (2" and 4" AX).

WHAT'S IN THE BOX

- AX/VX TOOL
- #4 SIZE HOSE (2)
- SPARE GRIP TAPE
- OPERATING & MAINTENANCE MANUAL

The gasket removal tool can be manufactured to accommodate a variety of industry standards or custom gasket sizes. It's designed to be positioned by the ROV manipulator, efficiently and reliably replacing standard 18 3/4-inch AX and VX style gaskets, and is manufactured using 100% corrosion-resistant alloys, ensuring resistance to corrosion damage and years of dependable subsea operation.

TECHNICAL SPECIFICATIONS

	WEIGHT (AIR)	WEIGHT (WATER)
18 3/4"	61 lbs.	54 lbs.
16 3/4"	56 lbs.	48 lbs.
15"	50 lbs.	42 lbs.
Materials	Stainless Steel Nickel-Aluminium-Bronze	